

The tilt enabling joints provide the means to position the lifting mechanisms above the main body of the aircraft and the means to tilt the primary and secondary lifting mechanisms in a plurality of directions and angles in a controlled manner 5 ~~manner~~ relative to the main body of the aircraft. Referring to the tilt enabling joint that can tilt the primary lifting mechanism as a primary tilt enabling joint, the primary lifting mechanism can be tilted forward, rearward, and from side to side with respect to the main body of the aircraft by 10 means of the primary tilt enabling joint. And referring to the tilt enabling joint that can tilt the secondary lifting mechanism as a secondary tilt enabling joint, the secondary lifting mechanism can be tilted forward, rearward, and from side to side with respect to the main body of the aircraft 15 by means of the secondary tilt enabling joint.

Tilting of the lifting mechanisms is used as a means to control the aircraft instead of varying blade pitches. By using tilting of lifting mechanisms to control the aircraft during flight, combinations of different forms of 20 lifting mechanisms can be used. For example, the front lifting mechanism can be in the form of a rotor with fixed pitch blades and an engine assembly, with the blades able to force air in a downward direction, while the rear lifting mechanism can be a jet engine which can force exhaust gases

~~directly~~ directly downward or downward and sideways, depending on the tilting of the jet. By being able to tilt the jet forward and rearward, and from side to side, changes in exhaust direction can be achieved. Sideway directed exhaust can be

5 used to counter the torque of the forward rotor during take off. Because the aircraft has a jet at the rear instead of a rotor, the downwash over the rear part of the body of the aircraft from rotor blades is avoided. As such wings can be fitted to the rear of the aircraft. On conventional

10 helicopters wings have been proven to be useless due to downwash from rotor blades. With wings fitted to the current invention, the aircraft could gain substantial lift during high speed forward flight, reducing the need to rely on the jet at the rear for lift. By fitting the forward lifting

15 rotor and engine to the main body of the aircraft with multiple tilt enabling joints, the forward lifting mechanism could be tilted 90 degrees forward during forward flight, thus overcoming the need for a counter torque mechanism during high speed forward flight. The jet can then be tilted

20 into a horizontal position, adding to forward propulsion. The aircraft in effect can be transformed into a high speed forward flying aeroplane, using a massive sized rotor at the front acting as a propeller on an aeroplane and a jet at the rear for forward propulsion. The wings would provide

turboprop, which is positioned on the secondary tilt enabling joint such that air can forced in a downward direction by means of the blades of the turboprop.

In another form of the aircraft the primary lifting  
5 mechanism comprises an engine assembly, a rotor, and blades connected to the rotor, with the engine assembly able to rotate the rotor and the blades connected to the rotor such that air can be forced to travel in a downward direction by means of the the blades rotating  
10 around the rotor, and the secondary lifting mechanism is a turboprop which is positioned on the secondary tilt enabling joint such that air can forced in a downward direction by means of the blades of the turboprop.

15 In another form of the aircraft the primary lifting mechanism is a turboprop which is positioned on the primary tilt enabling joint such that air can forced in a downward direction by means of the blades of the turboprop, while the secondary lifting mechanism comprises an  
20 engine assembly, a rotor, and blades connected to the rotor, with the engine assembly of the secondary lifting mechanism able to rotate the rotor of the secondary lifting mechanism and the blades of the secondary lifting mechanism connected to the rotor of the secondary lifting mechanism

In another form of the aircraft the primary lifting mechanism is a turboprop which is positioned on the primary tilt enabling joint such that air can forced in a downward direction by means of the blades of the  
5 turboprop, and the secondary lifting mechanism is a jet engine in the form of a turbojet that can be tilted so that exhaust from the turbojet can be forced in a downward direction behind the main body of the aircraft.

In another form of the aircraft the primary lifting  
10 mechanism is a turboprop which is positioned on the primary tilt enabling joint such that air can forced in a downward direction by means of the blades of the turboprop, and the secondary lifting mechanism is a jet engine in the form of a turbofan that can be tilted so  
15 that exhaust from the ~~turbofan~~ turbofan can be forced in a downward direction behind the main body of the aircraft.

In another form of the aircraft the primary lifting mechanism comprises an engine assembly, a rotor, and blades connected to the rotor, with the engine assembly  
20 able to rotate the rotor and the blades connected to the rotor such that air can be forced to travel in a downward direction by means of the blades rotating around the rotor, and the secondary lifting mechanism comprises two jet engines that can be tilted so that exhaust from the

activating mechanism comprises two hydraulic actuators connected to the movement enabling assembly and the main body of the aircraft.

In one form of the aircraft the secondary lifting mechanism  
5 ~~is pivotly~~ pivotally connected to the secondary tilt enabling joint such that the secondary lifting mechanism can be rotated on the secondary tilt enabling joint without the secondary tilt enabling joint having to move. In a form of the aircraft this rotating ability is achieved  
10 by means of a metal plate being used to join the secondary lifting mechanism to the upper section of the secondary tilt enabling joint, with the metal plate being joined to the upper section of the secondary tilt enabling joint by means of a large rivet, and an electric  
15 motor that turns a wheel is used to rotate the metal plate on the secondary tilt enabling joint, with the electric motor connected to the secondary tilt enabling joint and the wheel.

In another form of the aircraft the secondary tilt  
20 enabling joint is connected to the main body of the aircraft such that the secondary tilt enabling joint can be rotated on the aft end of the main body of the aircraft without components of the secondary tilt enabling joint having to move with respect to one another. In a form of the aircraft this rotating

ability is achieved by means of a metal plate being used to join the lower section of the secondary tilt enabling joint to the upper part of the aft end of the main body of the aircraft, with the metal plate being joined to the upper part of the main  
5 body by means of a large rivet which protrudes from inside of the main body of the aircraft. An electric motor that turns a wheel is used to rotate the metal plate that the secondary tilt enabling joint is attached to, with the electric motor connected to the upper section of the main body of the aircraft.

10

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows one form of aircraft according to this invention, comprising a rotor at the front and a rotor at the rear of the main body, with each rotor being able to be tilted in forward, rearward and lateral  
15 directions. The aircraft is shown in vertical take-off mode.

FIG. 2 shows an enlarged view of the lower part of the tilt enabling joint that connects the forward rotor to the main body, as viewed from behind.

FIG. 3 shows another form of the aircraft, with the forward  
20 lifting mechanism comprising a turboprop and the rear lifting mechanism also comprising a turboprop.

FIG. 4 shows another form of the aircraft, with the forward lifting mechanism comprising a rotor as shown in FIG. 1, and the rear lifting mechanism comprising a jet which is able to be titled in forward, rearward and lateral directions.

5 FIG. 5 shows the front of the lower part of the tilt enabling joint that joins the rear lifting mechanism to the main body of the aircraft.

FIG. 6 shows the aircraft of FIG. 4 now fitted with an additional forward tilt enabling joint.

10 FIG. 7 the aircraft of FIG. 6 with the aircraft now comprising a means to rotate the tilt enabling joint at the rear relative to the main body of the aircraft.

FIG. 8 shows the aircraft of FIG. 7 with wheels fitted to the main body, and a wing on the left side of the main body  
15 of the aircraft.

FIG. 9 shows the aircraft of FIG. 4 now comprising a means to rotate the jet at the rear relative to the tilt enabling joint at the rear.

FIG. 10 shows how the forward lifting mechanism can be  
20 placed in front of the main body of the aircraft, and how the lifting mechanism at the rear can be placed behind the main body of the aircraft.

FIG. 11 shows the aircraft of FIG. 1 with the engine assembly of the forward lifting mechanism now comprising two engines.

FIG. 12 shows the aircraft of FIG. 1 with the engine  
5 assembly of the rear lifting mechanism now comprising two engines.

FIG. 13 shows the aircraft of FIG. 1 with the engine assembly of the rear lifting mechanism now comprising two engines and the engine assembly of forward lifting mechanism  
10 also comprising two engines.

FIG. 14 shows a form of aircraft according to this invention with the engine assembly of the forward lifting mechanism of the aircraft of FIG. 1 comprising two engines, and the lifting mechanism at the rear comprising a turboprop.

15 FIG. 15 shows a form of aircraft according to this invention with the engine assembly of the rear lifting mechanism of the aircraft of FIG. 1 comprising two engines, and the lifting mechanism at the front comprising a turboprop.

FIG. 16 shows a form of aircraft according to this invention  
20 with the engine assembly of the forward lifting mechanism of the aircraft of FIG. 1 comprising two engines, and the lifting mechanism at the rear comprising a jet engine.



## DETAILED DESCRIPTION OF THE DRAWINGS

Figure 1 shows one form of the aircraft according to this invention. The aircraft has a main body 1 with a forward end 2 and an aft end 3. The ~~primary~~ primary lifting mechanism 4 comprises two blades 5, 6, connected to a rotor 7, which rotor 7 is rotated by means of an engine assembly 8 comprising one engine. The primary lifting mechanism 4 is connected to the top of the forward end 2 of the main body 1 by means of the primary tilt enabling joint 9 which has a movement enabling assembly in the form of a universal joint 10. A hydraulic actuator 11 is able to move the upper section 12 of the primary tilt enabling joint 9 forward and the hydraulic actuator 13 is able to move the upper section 12 of the primary tilt enabling joint in a rearward direction, while another hydraulic actuator 14 is connected to the main body 1 of the aircraft so that it is on the left side of the universal joint 10 and so that it is able to tilt a metal platform 15 which forms part of the universal joint 10 to the right side of the main body (Refer Figure 2).

Another ~~hydraulic~~ hydraulic actuator 16 is connected to the main body 1 of the aircraft so that it is on the right side of the universal joint and so that it can tilt the metal platform 15 to the left side of the main body of the aircraft. The hydraulic actuator 14 is positioned behind the universal joint 10 but is further forward on the main body than is the hydraulic actuator 16. The hydraulic actuators 14 and 16 are connected to the main body 1 and the metal platform 15 that forms part of the universal joint 10. The hydraulic actuators 11 and 13 are connected to the metal platform 15 and the upper section 12 of the primary tilt enabling joint 9. The secondary lifting mechanism 17 comprises blades 18, 19, connected to a rotor 20, which rotor 20 is rotated by means of an engine assembly 21 that comprises a single engine. The secondary lifting mechanism 17 is connected to the top of the aft end 3 of the main body 1 by means of the secondary tilt enabling joint 22 which has a movement enabling assembly in the form of a universal joint 23. A hydraulic actuator 24 is able to move the upper section 25 of the secondary tilt enabling joint 22 rearward with respect to the main body 1 and the hydraulic actuator 26 is able to move the upper section 25 of the secondary tilt enabling joint in a forward direction, while another hydraulic actuator 27 is connected to the main body 1 of the aircraft so that it is on the left side of the universal joint 23 and so that it is able to tilt a metal platform 28 which forms part of the universal

FIG. 11 shows the aircraft of FIG. 1 with the engine assembly of the forward lifting mechanism now comprising two engines.

FIG. 12 shows the aircraft of FIG. 1 with the engine  
5 assembly of the rear lifting mechanism now comprising two engines.

FIG. 13 shows the aircraft of FIG. 1 with the engine assembly of the rear lifting mechanism now comprising two engines and the engine assembly of forward lifting mechanism  
10 also comprising two engines.

FIG. 14 shows a form of aircraft according to this invention with the engine assembly of the forward lifting mechanism of the aircraft of FIG. 1 comprising two engines, and the lifting mechanism at the rear comprising a turboprop.

15 FIG. 15 shows a form of aircraft according to this invention with the engine assembly of the rear lifting mechanism of the aircraft of FIG. 1 comprising two engines, and the lifting mechanism at the front comprising a turboprop.

FIG. 16 shows a form of aircraft according to this invention  
20 with the engine assembly of the forward lifting mechanism of the aircraft of FIG. 1 comprising two engines, and the lifting mechanism at the rear comprising a jet engine.

joint 23 to the right side of the main body. Another hydraulic actuator 29 is connected to the main body 1 of the aircraft so that it is on the right side of the universal joint 23 so that it can tilt the metal platform 28 to the left side of the main  
5 body of the aircraft. The hydraulic actuator 27 is positioned further forward on the main body than is the hydraulic actuator 29. The hydraulic actuators 27 and 29 are connected to the main body 1 and the metal platform 28 that forms part of the universal joint 23. The hydraulic actuators 24 and 26 are connected to the  
10 metal platform 28 and the upper section 25 of the secondary tilt enabling joint 22. The universal joint 10 of the primary tilt enabling joint 9 is formed by transversely connecting hinges 30 and 31 by means of the metal platform 15. The universal joint 23 of the secondary tilt enabling joint 22 is formed by  
15 transversely connecting hinges 32 and 33 by means of the metal platform 28. The hinges 30 and 32 are joined to the upper part of main body 1 of the aircraft. By forcing air in a downward direction by means of the primary lifting mechanism and the secondary lifting mechanism the aircraft is able to achieve  
20 achieve vertical take-off. By tilting the primary lifting mechanism forward by means of the primary tilt enabling joint and tilting the secondary lifting mechanism forward by means of the secondary tilt enabling joint the aircraft is able to achieve forward flight as air is force downward and to the rear of the  
25 aircraft by the primary lifting mechanism and secondary lifting mechanism. The primary lifting mechanism and the secondary

lifting mechanism are arranged in tandem order above the main body 1, with the primary lifting mechanism forward of the secondary lifting mechanism. The primary tilt enabling joint and the secondary tilt enabling joint are also in tandem order on top 5 of the main body 1, with the primary tilt enabling joint in front of the secondary tilt enabling joint. The blades of the primary lifting mechanism protrude in front of the forward end of the main body 1.

Figure 2 shows the lower part of the primary tilt enabling 10 joint 9 at the forward end of the main body 1 of the aircraft of Figure 1. The view is from behind and shows the universal joint 10 as it would appear from behind, and the positioning of hydraulic hydraulic actuators 14 and 16, with hydraulic actuator 14 to 15 the left of the universal joint 10 and hydraulic actuator 16 to the right of the universal joint 10. The hydraulic actuators are connected to the metal plate 15 that forms part of the universal joint.

The hydraulic actuators 27 and 29 of the secondary tilt 20 enabling joint 22 of Figure 1 are distanced in the same manner from the universal joint 23 as the hydraulic actuators 14 and 16 are distanced from the universal joint 10 of the primary tilt enabling joint.

Figure 3 shows another form of the aircraft. The aircraft has a main body 1 as in figure 1, with a forward end 2 and an aft end 3. The primary tilt enabling joint 9 is the same as in Figure 1 and the secondary tilt enabling joint 22 is the same as in Figure 1. The primary lifting mechanism 4 is a turboprop 34 which can force air in a downward direction by means of the blades 35 and 36. The secondary lifting mechanism 17 is another turboprop 37 which can force air in a downward direction by means of the blades 38 and 39.

Figure 4 shows another form of the aircraft. The aircraft has a main body 1 with a forward end 2 and rear end 3. The primary lifting mechanism 4 is the same as in Figure 1 and the primary tilt enabling joint 9 is the same as in Figure 1. The secondary lifting mechanism 40 is a jet engine. The jet engine 40 is a turbojet and is attached to a hinge 41. The turbojet 40 is joined to metal plate 42 that forms of the hinge 41. A lower metal plate 43 forms part of the hinge 41. The lower metal plate 43 is connected to another hinge 44 that is positioned longitudinally on top of the main body 1. The lower hinge 44 is joined to the ~~the~~ upper part of the main body 1 of the aircraft. The hinges 41 and 44 are transversely connected. A hydraulic actuator 45 is connected to the metal plates 42 and 43 of hinge 41 such that it is able to tilt the turbojet 40 in a rearward direction by pushing the metal plate 42 in a rearward direction. A hydraulic actuator 46 is connected to the

lower metal plate 43 and the upper part of the main body and is connected to the main body 1 of the aircraft so that it is on the left of the lower hinge 44 such that it can tilt the lower plate 43 to the right. Another hydraulic actuator 47  
5 is connected to the upper part of the main body and the lower metal plate 43, and is connected to the main body 1 of the aircraft so that it is on the right side of the lower hinge 44 such that it can tilt the lower plate 43 to the left side of the main body 1. The metal plates 42, 43, the hinges 41 and 44,  
10 and the ~~hydraulic~~ hydraulic actuators 45, 46, and 47 form the secondary tilt enabling joint 22. The jet engine 40 is shown to be partly behind the main body 1 of the aircraft angled such that it forces exhaust gases in a downward direction through the rear  
15 48 of the turbojet 40. A turbofan jet engine could be used in place of the turbojet 40 positioned in the same manner as the turbojet 40.

Figure 5 shows the front of lower part of the secondary tilt enabling joint 22 of Figure 4 as ~~viewed~~ viewed from in front of  
20 the secondary tilt enabling joint 22. Figure 5 shows the lower hinge 44 connected to the lower plate 43 of Figure 4 and the main body 1 of the aircraft, and the distancing of the hydraulic actuators 46 and 47 from the lower hinge 44.

Figure 6 shows the aircraft of Figure 4 fitted with an  
25 additional tilt enabling joint 49, which is a third tilt

rivet 56 which is contained within the main body and protrudes from the main body 1 through an opening 57 in the upper part of the main body. The metal plate 55 is supported on metal blocks 58 and 59 such that the metal plate 55 can be rotated by an  
5 electric motor 60 rotating a wheel 61. Hydraulic actuators 46 and 47 are connected to the metal plate 55 and are in the same position with respect to the hinge 44 as they are in the aircraft of Figure 4. Figure 7 also shows a fin 62 attached to the jet engine 40. The jet is shown further behind the on the aft end  
10 of the main body of the aircraft then in Figure 6. The jet engine 40 could now be tilted in rearward direction so that it could be placed behind the main body of the aircraft.

Figure 8 shows the aircraft of Figure 7, now fitted with wheel assemblies 63 and 64. Wings can be fitted to the main  
15 body of the aircraft. Figure 6 shows the position of a wing 65 on the left side of the main body of the aircraft.

Figure 9 shows a variation of the aircraft of Figure 4. The upper metal plate 42 of the hinge 41 is longer, the jet engine 40 is attached to another metal plate 66, and a large rivet 67  
20 now joins the metal plate 66 to the metal plate 42, which rivet connects the metal plates 42 and 66 such that the metal plate 66 can pivately pivotally rotate with respect to the metal plate 42. A hydraulically hydraulically activated rotating arm 68 is used to rotate the metal plate 66 with respect to the metal plate 42. The  
25 rivet 67 and the hydraulically hydraulically activated rotating arm 68 combined



with the ~~additonal~~ additional metal plate 66 hence  
form a rotation enabling mechanism by which  
the jet engine 40 can be ~~pivety~~ pivotally rotated  
with respect to the secondary tilt enabling joint 22.

- 5 Figures 1, 3, 4 and 9 show that the aircraft can take-off  
and land vertically. Figure 8 shows that the aircraft can  
also take-off and land as a conventional forward flying  
aeroplane when fitted with wheels, wings, and when the  
tilt enabling joints have tilted the primary lifting  
10 mechanism and the secondary lifting mechanism forward.  
The aircraft could take-off while moving forward as an  
aeroplane and land as a helicopter, and vice versa.

- Figure 10 shows another form of the aircraft,  
with the whole of the primary lifting mechanism 4  
15 now in front of and above the forward end 2 of the  
main body 1. The secondary lifting mechanism 17 is  
now completely above and behind the aft end 3 of the  
main body 1. The primary tilt enabling joint 9  
and the secondary tilt enabling joint 22 are  
20 combinations of components of tilt enabling joints  
shown in previous figures. An addition is the  
extension platform 69 shown in respect of the primary  
tilt enabling joint 9 and the ~~extesion~~ extension  
platform 70 of the secondary tilt enabling joint 22.

FIG. 11 shows the aircraft of FIG. 1 with the engine assembly of the forward lifting mechanism now comprising two engines 71 and 72. In FIG. 1 the engine assembly of the forward lifting mechanism comprised a single engine.

5 FIG. 12 shows the aircraft of FIG. 1 with the engine assembly of the rear lifting mechanism now comprising two engines 73 and 74. In FIG. 1 the engine assembly of the rear lifting mechanism comprised a single engine.

FIG. 13 shows the aircraft of FIG. 1 with the engine  
10 assembly of the forward lifting mechanism now comprising two engines 75, 76, and the engine assembly of the rear lifting mechanism also comprising two engines 77 and 78.

FIG. 14 shows a variation of the aircraft of FIG. 1 with the engine assembly of the forward lifting mechanism of the aircraft  
15 of FIG. 1 now comprising two engines 79, 80, and the lifting mechanism at the rear now comprising a turboprop as was shown in FIG. 3.

FIG. 15 shows a variation of the aircraft of FIG. 1 with the engine assembly of the rear lifting mechanism of the aircraft of  
20 FIG. 1 now comprising two engines, 81, 82, and the lifting mechanism at the front comprising a turboprop as was shown in FIG. 3.

FIG. 16 shows a variation of the aircraft of FIG. 1 with the engine assembly of the forward lifting mechanism of the aircraft of FIG. 1 now comprising two engines, 83, 84, and the lifting mechanism at the rear comprising a jet engine as was shown in

5 FIG. 9.